

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(43) 国际公布日:
2005年6月9日(09.06.2005)

PCT

(10) 国际公布号:
WO 2005/053182 A1

(51) 国际分类号⁷: H04B 7/00, H01Q 1/00

(21) 国际申请号: PCT/CN2003/000999

(22) 国际申请日: 2003年11月25日(25.11.2003)

(25) 申请语言: 中文

(26) 公布语言: 中文

(71) 申请人(对除美国以外的所有指定国): 中兴通讯股份有限公司(ZTE CORPORATION) [CN/CN]; 中国广东省深圳市南山区高新技术产业园科技南路中兴通讯大厦, Guangdong 518057 (CN)。

(72) 发明人: 及

(75) 发明人/申请人(仅对美国): 李立林(LI, Lili) [CN/CN]; 向际鹰(XIANG, Jiying) [CN/CN]; 吴岩巍(WU, Yanwei) [CN/CN]; 中国广东省深圳市南山区高新技术产业园科技南路中兴通讯大厦, Guangdong 518057 (CN)。

(74) 代理人: 北京三友知识产权代理有限公司(BEIJING SANYOU INTELLECTUAL PROPERTY AGENCY LTD.); 中国北京市北三环中路40号, Beijing 100088 (CN)。

(81) 指定国(国家): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW


(84) 指定国(地区): ARIPO专利(BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI专利(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

本国际公布:
— 包括国际检索报告。

所引用双字母代码和其它缩写符号, 请参考刊登在每期PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: A METHOD AND APPARATU FOR IMPLEMENTING BEAM FORMING IN CDMA COMMUNICATION SYSTEM

(54) 发明名称: 一种用于码分多址系统实现波束成形的装置及方法



A BASEBAND SYSTEM
400, 432 OPTICAL INTERFACE BOARD
440 BUTTLER ARRAY

(57) Abstract: The present invention relates to a method and apparatus. For implementing beam forming in CDMA communication system. It provides a plurality of fixed beams formed within a sector. A plurality of fixed beams used in the same smart antennas system are formed narrow beam traffic channel and common channel having sector beam at the same time. It can overcome the differ from the change of time and temperature with phase of each path. So it need not complex technique of calibration. The capacity and performance in multi-antennas CDMA system have been improved. It resolves the problem that the coherent of each of fixed beams of space vector overlaps at some areas, when it transmits the common channel in multi-antennas CDMA system. The intensity of the polite channels and traffic channels becomes corresponding proportion; the received signal's ratio of the signal to noise is increased in mobile stations. The optical transceiver system is set between baseband and TRX; the more carriers are sustained in the baseband system. The distance between the device of radio frequency and the antenna is very close; the power cost is reduce.

[见续页]